

# 8160W DC CHAIN DRIVE WI-FI® GARAGE DOOR OPENER

Trusted reliability and quiet operation.



## KEY FEATURES

QUIET  
OPERATION  
DC Motor

WI-FI  
Built In



myQ integrates with leading smart home platforms.  
Visit [myQ.com](https://myQ.com) to learn more.

## INCLUDED ACCESSORIES:

### MULTI-FUNCTION CONTROL PANEL®

Includes lockout controls and  
accessory programmability.



882LMW

### 3-BUTTON REMOTE CONTROL

Operates up to 3 openers.



893LM

## POWERFUL ADD-ONS:

### myQ HOME BRIDGE

Adds Apple® HomeKit™ compatibility  
and Siri® voice control to Wi-Fi-enabled  
openers. Installs easily in the garage  
within Wi-Fi range.\*



819LMB

### MINI UNIVERSAL REMOTE CONTROL

Compact and portable to provide  
quick, easy garage access.



374UT

## RELIABLE

**DC MOTOR** IS PURPOSEFULLY DESIGNED FOR QUIET PERFORMANCE.

**CHAIN DRIVE SYSTEM** FOR STEADY PERFORMANCE AND  
INDUSTRIAL STRENGTH.

**SOFT START/STOP** FOR SMOOTH OPERATION.

**WARRANTY** 4-YEAR MOTOR, 1-YEAR PARTS AND ACCESSORIES.

## SMART

**BUILT-IN WI-FI** FOR THE EASIEST WAY TO CONNECT THE GARAGE.

**myQ MOBILE APP** LETS USERS RECEIVE ALERTS AND CONTROL THE  
OPENER FROM ANYWHERE.

## SECURE

**SECURITY+ 2.0®** SENDS A NEW CODE WITH EVERY REMOTE CLICK.

**POSILOCK®** ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

**ALERT-2-CLOSE** SIGNALS WHEN A DOOR IS BEING CLOSED BY MyQ.

**THE PROTECTOR SYSTEM®** INVISIBLE LIGHT BEAM AUTO-REVERSES  
THE DOOR IF THERE IS AN OBSTRUCTION.

\*Controlling this HomeKit-enabled accessory automatically and away from home requires an Apple TV® with  
tvOS™ 10.0 or later or an iPad® with iOS 10.0 or later set up as a home hub.  
Smartphone not included.

PRODUCT GUIDE 8160W

DC CHAIN DRIVE WI-FI  
GARAGE DOOR OPENER

**LiftMaster®**

# MASTERFUL ENGINEERING.

8160W

DC CHAIN DRIVE WI-FI®  
GARAGE DOOR OPENER

## MOTOR



- 12V DC
- 53 RPM
- Automatic Thermal Protection
- Permanent Lubrication

## POWER



- 120V AC
- 60 Hz Voltage
- 2.7A Current Rating
- UL® Listed
- 4' Power Cord (3-Prong)

## MECHANICS



- **Steel Chassis, T-Rail and Trolley**
- **Full Chain Drive Mechanism** (63:1 Gear Reduction and Adjustable Door Arm)
- **Auto-Force** Adjustment for Changing Weather and Environmental Conditions
- **Electronic Limits** for Easy Setup
- **DC Wi-Fi Logic Board** with Built-In Surge Suppressor (for Replacement Logic Boards, Order Part 050DCTWF)

7.67"



15.2"

10.5"

## DIMENSIONS

| Rail Options     | 7'   | 8'   | 10'   |
|------------------|------|------|-------|
| Installed Length | 128" | 140" | 164"  |
| Max. Opening     | 7'6" | 8'6" | 10'6" |

Headroom Clearance Required: 2"

8.5"

Per second  
for door  
to move  
upward

SPEED

6.5"

Per second  
for door  
to move  
downward

## STANDARD SPECS.

SECURITY

### SECURITY+ 2.0® RADIO CONTROLS

3-Button Remote Control (893LM)

Operating Range: ~200'

Operating Temperature: -30°F to 150°F  
Frequency:

- Remote Controls: Security+ 2.0
- Garage Door Opener: Security+ 2.0
- Security+ 2.0 Anti-Burglary Coding

SMART

### myQ® RADIO

902-928 MHz  
50-Channel FHSS  
(Frequency Hopping Spread Spectrum)

- Provides 2-way communication from garage door opener and myQ Accessories.
- Enables monitoring and control of garage door openers via smartphone or tablet.

ELECTRICAL

### LIGHTING



- Max. 1 100-Watt Lightbulb
- Adjustable-Time Solid-State Delay
- Enhanced CFL (Compact Fluorescent) Compatible, Max. 26 Watts

### SECURITY+ 2.0

#### ENCRYPTED CONTROLS

Multi-Function Control Panel® (882LMW)

- Program Remote Controls
- Maintenance Alert System
- Easy Wi-Fi Setup

### HOMELINK® COMPATIBLE

#### (VERSION 4.0 OR HIGHER\*)

\*May require an external adapter depending on the model and year of your vehicle. Visit [HomeLink.com](http://HomeLink.com) for additional information.

## SHIPPING.

SHIPPING WEIGHT (in lbs.)



18  
HEAD



20  
RAIL (7')

### CARTONS (2)

CARTON 1: 20" x 12" x 10"

- Multi-Function Control Panel (882LMW)
- 3-Button Remote Control (893LM)
- Garage Door Opener Head (8160W)
- The Protector System® Safety Reversing Sensors

CARTON 2: 10'4" x 5" x 5" (for 7' Rail)

- Assembled Solid-Steel Chain T-Rail

## CONVENIENCE AND SAFETY.

- Alert-2-Close with Unattended Close Operation†
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening
- Down Safety Reverse
- Up Safety Stop
- Maintenance Alert System
- Garage Door Opener Capacity of up to 12 Remote Controls, 1 Keyless Entry System and 16 myQ Devices



\*WARNING: to reduce the risk of injury to persons—ONLY enable Timer-to-Close and myQ remote operation features when opener is installed on a sectional door.

©2022 Chamberlain Group LLC. All Rights Reserved. LiftMaster, the LiftMaster logo, myQ® and the myQ® logo are registered trademarks of The Chamberlain Group LLC. 300 Windsor Drive, Oak Brook, IL 60523

LiftMaster.com  
Wi-Fi® is a registered trademark of Wi-Fi Alliance  
UL® and the UL logo are trademarks of UL LLC © 2022 All Rights Reserved.  
LMGDENPG8160W\_202201\_MC21

LiftMaster®